



meccalte



HCP 3

MECCALTE spa - Via Roma, 20 - 36051 CREAZZO (VI) ITALIA
 Tel. +39 0444/396111 - Fax. +39 0444/396166 - e-mail: info@meccalte.it
 web site: www.meccalte.com

14 POLI

400 Hz 3428 r.p.m.

CHARACTERISTICS

ambient 40° C

| Type | KVA - cos φ 0.8 - 3 Phase continuous | | | Efficiency | | |
|--------------------------------|--------------------------------------|------|-------------------|-----------------------|------|------|
| | CL. H (ΔT= 125°C) | | CL. F (ΔT= 105°C) | η % CL. H (ΔT= 125°C) | | |
| Series Star Λ | 415 | IP45 | 415 | 2/4 | 3/4 | 4/4 |
| Parallel Star $\Lambda\Lambda$ | 208 | | 208 | | | |
| Series Delta Δ | 240 | | 240 | | | |
| Parallel Delta $\Delta\Delta$ | 120 | | 120 | | | |
| HCP3-1S/14 | 5,5 | 4,5 | 5 | 82,1 | 83,8 | 83,5 |
| HCP3-2S/14 | 7 | 5,5 | 6,5 | 83 | 84,6 | 84,4 |
| HCP3-3S/14 | 9 | 7 | 8,5 | 83,8 | 85,4 | 85,1 |
| HCP3-2L/14 | 11 | 8,5 | 10 | 84,2 | 85,8 | 85,5 |
| HCP3-3L/14 | 13 | 10 | 12 | 84,7 | 86,2 | 86 |

| Type | J (Kgm ²) B3-B14 FORM | Weight B3-B14 (Kg) | Air Volume (m ³ /min) 3428 rpm | Noise dB(A) | |
|------------|---|-----------------------|---|-------------|----|
| | | | | 3428 rpm | |
| | | | | 1m | 7m |
| HCP3-1S/14 | 0,0584 | 49 | 6,9 | 87 | 72 |
| HCP3-2S/14 | 0,0726 | 54 | 6,8 | | |
| HCP3-3S/14 | 0,0939 | 61 | 6,8 | | |
| HCP3-2L/14 | 0,1152 | 72 | 6,6 | | |
| HCP3-3L/14 | 0,1436 | 80 | 6,5 | | |

ACCESSORIES

| REGULATOR | | PARALLEL DEVICE | THERMAL PROTECTION | | | HEATERS | MECHANICAL PROTECTION | | | |
|--------------|-----------|--------------------|--------------------|--------------|-------|---------|-----------------------|------|------|------|
| UVR6/1-H400B | SR7/H400B | | PTC | BIMET DEVICE | PT100 | | IP21 | IP23 | IP45 | IP55 |
| ● | □ | □ | □ | □ | □ | □ | ● | □ | □ | |

● = Standard □ = Optional

Rating



